

# EXTREME VR2



A modern competition road legal semi-slick tyre with asymmetric tread and shoulder design. The outside structure of this tyre increases the grip and precision while cornering, whereas the inside structure provides maximum road contact on the straight line. Together with reinforced sidewalls and advanced compounds the VR2 offers supreme grip and immediate steering response.

## PRODUCT PREVIEW

## TECHNICAL SPECIFICATION

**TABLE 1: DIMENSIONS**

\* - H index applies to Type-W compounds \*\* - Type-R&W / Type-S

| Tyre Size  | Load/Speed Index | Recommended rim width [inch] | Approx. Weight** [kg] | Tread Depth [mm] | Overall Diameter [mm] | Tread Width [mm] |
|------------|------------------|------------------------------|-----------------------|------------------|-----------------------|------------------|
| 185/60 R13 | 80 H             | 6.0/6.5                      | 8.3                   | 5.0              | 548                   | 185              |
| 205/60 R13 | 86 H             | 6.5/7.0                      | 9.5                   | 5.0              | 570                   | 190              |
| 175/50 R13 | 72 H             | 6.0/6.5                      | 6.5                   | 5.0              | 501                   | 175              |
| 215/50 R13 | -                | -                            | -                     | 5.0              | -                     | -                |
| 185/55 R14 | 80 H             | 6.0/6.5                      | 7.8                   | 5.0              | 552                   | 185              |
| 195/55 R15 | 85 H             | 6.5/7.0                      | 9.2                   | 5.0              | 590                   | 185              |
| 195/50 R15 | 82 H             | 6.5/7.0                      | 8.7                   | 5.0              | 574                   | 195              |
| 205/55 R16 | 91 H             | 6.5/7.0                      | 9.3/8.7               | 5.0              | 625                   | 195              |
| 195/50 R16 | 88 H             | 6.5/7.0                      | 8.8                   | 5.0              | 595                   | 190              |
| 205/50 R16 | 87 H             | 7.0/7.5                      | 9.8                   | 5.0              | 605                   | 204              |
| 205/45 R17 | 84 H/V*          | 7.0/7.5                      | 9.3                   | 5.0              | 609                   | 200              |
| 215/45 R17 | 87 V             | 7.5/8.0                      | 10.5                  | 5.0              | 625                   | 207              |
| 225/45 R17 | 91 H/V*          | 8.0/8.5                      | 11.5/10.5             | 5.0              | 630                   | 218              |
| 245/40 R17 | 91 V             | 9.0/9.5                      | 11.1                  | 5.0              | 625                   | 240              |
| 225/40 R18 | 88 H/V*          | 8.0/8.5                      | 11.5/10.5             | 5.0              | 635                   | 230              |
| 235/40 R18 | 91 V             | 8.5/9.0                      | 11.5                  | 5.0              | 639                   | 240              |
| 255/35 R18 | 90 H/W*          | 9.0/9.5                      | 12.0                  | 5.0              | 631                   | 255              |
| 265/35 R18 | 93 H/W*          | 9.5/10.0                     | 12.5/12.0             | 5.0              | 633                   | 260              |
| 285/35 R18 | 97V              | 10.5/11.0/11.5               | 13.7                  | 5.0              | 665                   | 270              |
| 235/35 R19 | 91 V             | 8.5/9.0                      | 10.8                  | 5.0              | 641                   | 240              |

**TABLE 2: RUBBER COMPOUNDS**

| Version    | Hardness   | Application           | Compound Operating Temperature [°C] | Treadwear Indication |
|------------|------------|-----------------------|-------------------------------------|----------------------|
| TYPE - W3A | SUPER SOFT | DRY/DAMP SURFACE      | 0 - 30                              | 50                   |
| TYPE - R5A | SOFT       | DRY/DAMP SURFACE      | 15 - 50                             | 80                   |
| TYPE - R7A | MEDIUM     | DRY SURFACE           | 30 - 80                             | 140                  |
| TYPE - R9A | HARD       | DRY SURFACE           | 50 - 110                            | 200                  |
| TYPE - S3  | MEDIUM     | STREET / PRACTICE     | 30 - 90                             | 220                  |
| TYPE - HL  | MEDIUM     | HOT-LAP / TIME ATTACK | 40-70                               | 50                   |