

X EXTREME VR3



PRODUCT PREVIEW

Full-wet rain tyre, providing exceptional traction and precision on **wet and dirty surfaces**. The directional tread pattern has been developed for the most effective draining of water from the tyre and road contact surface. **The rubber compound in this model has been especially modified** in order to maximize performance in rainy conditions.

TECHNICAL SPECIFICATION

TABLE 1: DIMENSIONS

Tyre Size	Load/Speed Index	Recommended rim width [inch]	Approx. Weight [kg]	Tread Depth [mm]	Overall Diameter [mm]	Tread Width [mm]
205/60 R13	86 H	6.0/6.5/7.0	9,9	6,5	573	186
175/50 R13	72 H	5.5/6.0/6.5	6.1	6,5	504	170
195/50 R15	82 H	6.5/7.0	8,7	6,5	574	187
195/50 R16	84 H	6.5/7.0	9.0	6,5	600	190
205/45 R17	84 H	7.0/7.5	9.4	6,5	616	195
225/45 R17	91 H	7.5/8.0	10.3	6,5	630	210
225/40 R18	91 H	7.5/8.0	10.0	6,5	632	213

* - in progress

TABLE 2: RUBBER COMPOUNDS

Version	Hardness	Application	Compound Operating Temperature [°C]	Treadwear Indication
TYPE - W3A	SUPER SOFT	FULL WET SURFACE	0 - 30	50